

TND-2026-0268

Technical & Commercial Proposal — MR 28857

67 items · Libya

Buyer	ACG Industrial & Infrastructure Solutions (ACG IIS)
Tender Reference	TND-2026-0268
Due Date	30 Oct 2026
Published Via	Tenderion — NOVA Platform Marketplace

Technical Specifications

CLIN 0001	RS PRO Adjustable Spanner, 304.8 mm Overall, 34mm Jaw Capacity, Metal Handle
-----------	--



RS PRO Adjustable Spanner, 304.8 mm Overall, 34mm Jaw Capacity, Metal Handle

Qty: 2 EA
Brand
RS PRO
MFR / Part #
541-6602

SPECIFICATIONS

Wrench Type	Adjustable Spanner
Jaw Capacity	34mm
Overall Length	304.8 mm
Handle Type	Metal
Material	Chrome Vanadium Steel

CLIN 0002

RS PRO Pipe Wrench, 609 mm Overall, 75mm Jaw Capacity, Metal Handle

Image
unavailable

View online !—

RS PRO Pipe Wrench, 609 mm Overall, 75mm Jaw Capacity, Metal Handle

Qty: 2 EA

Brand

RS PRO

MFR / Part #

260-3005

SPECIFICATIONS

Wrench Type	Pipe Wrench
Jaw Capacity	75mm
Overall Length	609 mm
Non Sparking	No
Handle Type	Metal
Finish	Painted
VDE/1000V Approved	No
Material	Carbon Steel

CLIN 0003

RS PRO Pipe Wrench, 305 mm Overall, 44mm Jaw Capacity, Metal Handle

Image
unavailable

View online !—

RS PRO Pipe Wrench, 305 mm Overall, 44mm Jaw Capacity, Metal Handle

Qty: 2 EA

Brand

RS PRO

MFR / Part #

260-3003

SPECIFICATIONS

Wrench Type	Pipe Wrench
Jaw Capacity	44mm
Overall Length	305 mm
Non Sparking	No
Handle Type	Metal
Finish	Painted
VDE/1000V Approved	No
Material	Carbon Steel

CLIN 0004

Durable Red A4, 323mm Height (1 pack of 5 units)



Durable Red A4, 323mm Height (1 pack of 5 units)


Qty: 1 pack (1 pack of 5 units)
Brand
Durable
MFR / Part #
486903

SPECIFICATIONS

Height	323mm
Colour	Red
Document Size	A4

CLIN 0005

RS PRO 10-Piece Box Wrench Set, 8 !' 27 mm, Chrome Vanadium Steel



RS PRO 10-Piece Box Wrench Set, 8 !' 27 mm, Chrome Vanadium Steel


Qty: 1 EA
Brand
RS PRO
MFR / Part #
388-3735

SPECIFICATIONS

Set Type	Flex Head Socket Spanner Set
Sizes in Set	8 !' 27 mm
Number of Pieces	10
Material	Chrome Vanadium Steel
Finish	Chrome

CLIN 0006

RS PRO Nut Splitter For Nut Sizes 3/8"" !' 1-7/8""



RS PRO Nut Splitter For Nut Sizes 3/8"" !' 1-7/8""

Qty: 1 EA
Brand
RS PRO
MFR / Part #
423-6691

SPECIFICATIONS

Supported Nut Size	3/8"" !' 1-7/8""
--------------------	------------------

CLIN 0007

RS PRO 200mm, 8in Digital Caliper Caliper 0.0005 in, 0.01 mm Resolution, Imperial, Metric

Image
unavailable

View online !—

RS PRO 200mm, 8in Digital Caliper Caliper 0.0005 in, 0.01 mm Resolution, Imperial, Metric

Qty: 1 EA

Brand

RS PRO

MFR / Part #

243-6617

SPECIFICATIONS

Caliper Type	Digital Caliper
Capacity	200mm, 8in
Imperial or Metric	Imperial, Metric
Display Type	Digital
Accuracy	0.03 mm
Resolution	0.0005 in, 0.01 mm

CLIN 0008

RS PRO Phillips; Slotted Precision Screwdriver Set, 11-Piece

Image
unavailable

View online !—

RS PRO Phillips; Slotted Precision Screwdriver Set, 11-Piece

Qty: 2 EA

Brand

RS PRO

MFR / Part #

537-883

SPECIFICATIONS

Screwdriver Type	Precision Screwdriver Set
Number of Pieces	11
Tip Type	Phillips; Slotted
Tip Size	Slotted: 1; 1.2; 1.4; 1.8; 2.4; 3 mm; Phillips: PH0; PH1; PH2; PH3; PH4

CLIN 0009

RS PRO Carbon Steel Lump Hammer with Fibreglass Handle, 1kg

Image
unavailable

View online !—

RS PRO Carbon Steel Lump Hammer with Fibreglass Handle, 1kg

Qty: 2 EA

Brand

RS PRO

MFR / Part #

125-0941

SPECIFICATIONS

Hammer Type	Lump Hammer
Head Material	Carbon Steel
Handle Material	Fibreglass
Weight	1kg

CLIN 0010

Chauvin Arnoux CA 10001 pH Meter, 0.01pH Resolution, 14pH Max, +60 °C Max

Image
unavailable

View online !—

Chauvin Arnoux CA 10001 pH Meter, 0.01pH Resolution, 14pH Max, +60 °C Max

Qty: 2 EA

Brand

Chauvin Arnoux

MFR / Part #

P01710015

SPECIFICATIONS

Maximum pH	14pH
Minimum pH	0pH
pH Resolution	0.01pH
Maximum Temperature Measurement	+60 °C
Minimum Temperature Measurement	0°C
Weight	65g
Height	227mm
Maximum Operating Temperature	+50°C
Dimensions	20 x 36 x 227mm
Model Number p	CA 10001
Minimum Operating Temperature	0°C
Battery Type	CR232
Width	36mm
Battery Life	>100 h
Length	20mm
Model Number (p)	CA 10001

CLIN 0011

RS PRO 5m Tape Measure, Metric & Imperial



RS PRO 5m Tape Measure, Metric & Imperial


Qty: 2 EA
Brand
RS PRO
MFR / Part #
192-3658

SPECIFICATIONS

Length	5m
Blade Width	19 mm
Imperial or Metric	Imperial, Metric

CLIN 0012

RS PRO 3-Piece Locking Plier Set, 250 mm Overall



RS PRO 3-Piece Locking Plier Set, 250 mm Overall


Qty: 2 EA
Brand
RS PRO
MFR / Part #
847-3768

SPECIFICATIONS

Plier Types in Set	Locking Pliers
Number of Pieces	3
Material	Chrome Vanadium Steel
Overall Length	250 mm

CLIN 0013

RS PRO 4-Piece Plier Set, 250 mm Overall



RS PRO 4-Piece Plier Set, 250 mm Overall

Qty: 2 EA
Brand
RS PRO
MFR / Part #
668-5880

SPECIFICATIONS

Plier Types in Set	Combination Pliers, Cutters, Long Nose Pliers, Water Pump Pliers
Number of Pieces	4
Material	Chrome Vanadium Steel
Overall Length	250 mm

CLIN 0014

RS PRO 6-Piece Gripping Plier Set, ESD, 150 mm Overall



RS PRO 6-Piece Gripping Plier Set, ESD, 150 mm Overall


Qty: 1 EA
Brand
RS PRO
MFR / Part #
864-0814

SPECIFICATIONS

Plier Types in Set	Flat Nose Pliers
Number of Pieces	6
Material	High Carbon Steel
ESD Safe	Yes
Overall Length	150 mm

CLIN 0015

RS PRO 82 Piece Mechanical Tool Kit with Box



RS PRO 82 Piece Mechanical Tool Kit with Box

Qty: 1 EA
Brand
RS PRO
MFR / Part #
136-3412

SPECIFICATIONS

Set Type	Mechanical
Set Contents	Chisel, Cutters, Feeler Gauges, Hammer, Hex Keys, Knife, Pliers, Punch, Ratchet, Screwdriver, Sockets, Spanners, Tape Measure, Voltage Tester
Number of Pieces	82
VDE/1000V Approved	No
Storage Type	Box

CLIN 0016

RS PRO 12000rpm Air Angle Grinder



RS PRO 12000rpm Air Angle Grinder

Qty: 1 EA
Brand
RS PRO
MFR / Part #
739-8389

SPECIFICATIONS

Grinder Type	Air Angle Grinder
Speed	12000rpm

CLIN 0017

Jack Sealey BG200XL Bench Grinder 200mm, 230V



Jack Sealey BG200XL Bench Grinder 200mm, 230V

Qty: 1 EA
Brand
Jack Sealey
MFR / Part #
BG200XL

SPECIFICATIONS

Grinding Wheel Bore	16mm
Grinding Wheel Diameter	200mm
Speed	3200rpm
Voltage Rating	230V
Motor Wattage	560W
Plug Type	Type G - British
Model Number	BG200XL

CLIN 0018

DeWALT SDS Plus 240V Corded SDS Drill, UK Plug



DeWALT SDS Plus 240V Corded SDS Drill, UK Plug


Qty: 1 EA
Brand
DeWALT
MFR / Part #
D25033K-GB

SPECIFICATIONS

Drill Type	SDS Drill
Voltage Rating	240V
Corded/Cordless	Corded
Brushed/Brushless Motor	Brushed
Chuck Type	SDS Plus
Orientation	Straight
Weight	2.5kg
Wattage	710W
Plug Type	Type G - British 3-pin
Model Number	D25033K-GB

CLIN 0019

Bahco Adjustable Spanner, 30mm Jaw Capacity, Metal Handle



Bahco Adjustable Spanner, 30mm Jaw Capacity, Metal Handle

Qty: 1 EA
Brand
Bahco
MFR / Part #
ADJUST 3

SPECIFICATIONS

Wrench Type	Adjustable Spanner
Jaw Capacity	30mm
Handle Type	Metal
Number of Pieces	3

CLIN 0020

Bahco S4RM Series 5-Piece Spanner Set, 8 x 9 !' 34 x 36 mm



Bahco S4RM Series 5-Piece Spanner Set, 8 x 9 !' 34 x 36 mm


Qty: 1 EA
Brand
Bahco
MFR / Part #
S4RM/5T

SPECIFICATIONS

Set Type	Ratchet Spanner Set
Series	S4RM
Sizes in Set	8 x 9 !' 34 x 36 mm
Number of Pieces	5
VDE/1000V Approved	No

CLIN 0021

Bahco 111M Series 17-Piece Spanner Set, 8 !' 32 mm, Alloy Steel



Bahco 111M Series 17-Piece Spanner Set, 8 !' 32 mm, Alloy Steel

Qty: 2 EA
Brand
Bahco
MFR / Part #
111M/17TL

SPECIFICATIONS

Set Type	Combination Spanner Set
Series	111M
Sizes in Set	8 !' 32 mm
Number of Pieces	17
Material	Alloy Steel
VDE/1000V Approved	No
Finish	Chrome

CLIN 0022

RS PRO 9 piece L Shape Metric Hex Key Set, 1.5mm

Image
unavailable

View online !—

RS PRO 9 piece L Shape Metric Hex Key Set, 1.5mm

Qty: 2 EA

Brand

RS PRO

MFR / Part #

144-7564

SPECIFICATIONS

Product Type	Hex Key Set
Imperial or Metric	Metric
Number of Pieces	9
Hex Key Size	1.5 mm, 2.0 mm, 2.5 mm, 3.0 mm, 4.0 mm, 5.0 mm, 6.0 mm, 8.0 mm, 10.0mm
Shape	L
Tip Type	Ball End Hexagon
Short or Long Arm	Extra Long
Material	Chrome Vanadium Steel

CLIN 0023

RS PRO 13 piece L Shape Imperial Hex Key Set, 0.05 !" 3/8in

Image
unavailable

View online !—

RS PRO 13 piece L Shape Imperial Hex Key Set, 0.05 !" 3/8in

Qty: 2 EA

Brand

RS PRO

MFR / Part #

151-1507

SPECIFICATIONS

Product Type	Hex Key Set
Imperial or Metric	Imperial
Number of Pieces	13
Hex Key Size	0.05 !" 3/8in
Shape	L
Tip Type	Ball End Hexagon
Short or Long Arm	Long
Material	Chrome Vanadium Steel

CLIN 0024

Bahco 103-Piece Metric 1/2 in; 1/4 in Deep Socket/Standard Socket/Spanner/Allen Key/Bit Set with Ratchet, 6 point: Hex



Bahco 103-Piece Metric 1/2 in; 1/4 in Deep Socket/Standard Socket/Spanner/Allen Key/Bit Set with Ratchet, 6 point: Hex

Qty: 1 EA

Brand

Bahco

MFR / Part #

S103

SPECIFICATIONS

Socket Set Type	Deep Socket/Standard Socket/Spanner/Allen Key/Bit Set
Drive Size	1/2 in; 1/4 in
Imperial or Metric	Metric
Number of Pieces	103
Socket Head Type	6 point; Hex Bit; Phillips Bit; Pozidriv Bit; Torx Bit
Ratchet Included	Yes
Socket Size	4 !' 13mm
Material	Alloy Steel

CLIN 0025

7000psi Steel Manual Grease Gun, 16 oz



7000psi Steel Manual Grease Gun, 16 oz

Qty: 2 EA

Brand

RS PRO

MFR / Part #

672-166

SPECIFICATIONS

Capacity	16 oz
Material	Steel
Maximum Pressure	7000psi

CLIN 0026

Stanley Tools Phillips; Pozidriv; Slotted Screwdriver Set, 20-Piece



Stanley Tools Phillips; Pozidriv; Slotted Screwdriver Set, 20-Piece

Qty: 1 EA

Brand

Stanley Tools

MFR / Part #

1-65-XXX

SPECIFICATIONS

Screwdriver Type	Standard Screwdriver Set
Number of Pieces	20
Tip Type	Phillips; Pozidriv; Slotted
Tip Size	Slotted: 2.5; 3; 4; 4; 5.5 mm; Flared: 4; 5.5; 6.5; 8 mm; Phillips: PH00; PH0; PH1; PH1; PH2; PH3; Pozidriv: PZ0; PZ1; PZ2; PZ2; PZ3

CLIN 0027

DeWALT 1/2 in 18V, 5Ah Impact Wrench, Euro Plug



DeWALT 1/2 in 18V, 5Ah Impact Wrench, Euro Plug

Qty: 1 EA

Brand

DeWALT

MFR / Part #

DCF891P2T-QW

SPECIFICATIONS

Voltage Rating	18V
Drive Size	1/2 in
Impact Rate	0 +b 3250bpm
Brushed/Brushless Motor	Brushless
Plug Type	Type C - Euro Plug
Number of Batteries Supplied	2
Battery Capacity	5Ah
Speed	600 rpm, 1200 rpm, 2000rpm
Weight	2.22kg
Model Number	DCF891P2T

CLIN 0028

Knipex 8-Piece Circlip Plier Set, 12 in Overall



Knipex 8-Piece Circlip Plier Set, 12 in Overall

Qty: 1 EA
Brand
Knipex
MFR / Part #
00 20 04 V01

SPECIFICATIONS

Plier Types in Set	Circlip Pliers
VDE/1000V Approved	No
Number of Pieces	8
Material	Chrome Vanadium Steel
ESD Safe	No
Height Safe	No
Overall Length	12 in

CLIN 0029

RS PRO APT205 1/2 in Air Impact Wrench, 7500rpm, 540Nm



RS PRO APT205 1/2 in Air Impact Wrench, 7500rpm, 540Nm

Qty: 1 EA
Brand
RS PRO
MFR / Part #
739-8379

SPECIFICATIONS

Air Tool Type	Air Impact Wrench
Drive Size	1/2 in
Maximum Torque	540Nm
Speed	7500rpm
Length	190mm
Model Number	APT205

CLIN 0030

SIMPLEX Hand Pump: 2 Stages, Single Acting, 200 psi Max. Pressure 1st Stage, Aluminum

A manual hand pump with a black handle and a silver body. The pump has a cylindrical reservoir and a handle with a textured grip. The brand name 'SIMPLEX' and model 'P30' are visible on the side.

SIMPLEX Hand Pump: 2 Stages, Single Acting, 200 psi Max. Pressure 1st Stage, Aluminum

Qty: 1 EA

Brand

SIMPLEX

MFR / Part #

P30

SPECIFICATIONS

Manufacturer Model	P30
Grainger Item Number	825YD6
Number of Stages	2 (Two-Speed Auto-Switching)
Cylinder Compatibility	Single-Acting
Pump Power Source	Manual
Reservoir Material	Anodized Aluminum
Housing & Handle Material	Aluminum
Working Orientation	Horizontal and Vertical
Maximum Operating Pressure (2nd Stage)	3,000 psi (207 bar)
Maximum Pressure (1st Stage)	200 psi (14 bar)
Oil Displacement per Stroke (1st Stage)	0.91 cu in (14.9 cm³)
Oil Displacement per Stroke (2nd Stage)	0.19 cu in (3.1 cm³)
Usable Oil Capacity	30 cu in (491.6 cm³)
Maximum Handle Effort	26 kg (57.3 lbs)
Outlet Connection Size	3/8 inch
Outlet Connection Type	FNPT

CLIN 0031

SIMPLEX Hand Pump: 2 Stages, Single Acting, 200 psi Max. Pressure 1st Stage



SIMPLEX Hand Pump: 2 Stages, Single Acting, 200 psi Max. Pressure 1st Stage

Qty: 1 EA

Brand

SIMPLEX

MFR / Part #

P42

SPECIFICATIONS

Manufacturer Model	P42
Grainger Item Number	825YD8
Product Series	P Steel Series
Number of Stages	2 (Two-Speed Auto-Switching)
Cylinder Compatibility	Single-Acting
Pump Power Source	Manual
Reservoir Material	Heavy-Duty Compact Steel
Working Orientation	Horizontal and Vertical
Maximum Operating Pressure (2nd Stage)	10,000 psi (700 bar)
Maximum Pressure (1st Stage)	200 psi (14 bar)
Oil Displacement per Stroke (1st Stage)	0.79 cu in (12.95 cm³)
Oil Displacement per Stroke (2nd Stage)	0.17 cu in (2.79 cm³)
Usable Oil Capacity	39 cu in (639.1 cm³)
Total Reservoir Capacity	45 cu in (737.4 cm³)
Maximum Handle Effort	42 kg (92.6 lbs)
Outlet Connection Size	3/8 inch
Outlet Connection Type	FNPT

CLIN 0032

Hydraulic Hose Assembly: 1/4 in ID, NPTF x NPTF, 3 ft Lg, Yellow, 3/8 in x 3/8 in Fitting Size



Hydraulic Hose Assembly: 1/4 in ID, NPTF x NPTF, 3 ft Lg, Yellow, 3/8 in x 3/8 in Fitting Size

Qty: 1 EA

Brand

ENERPAC

MFR / Part #

H7203

SPECIFICATIONS

Manufacturer Model	H7203
Grainger Item Number	46C580
Hose Series	H700-Series Safety Hoses
Material Construction	Polyurethane Outside Jacket (Two Layers of Steel Wire Braid)
Hose Color	Yellow
Design / Safety Factor	4:1
Maximum Operating Pressure	10,000 psi (700 bar)
Hose Internal Diameter (ID)	1/4 inch (6.4 mm)
Hose Length	3 feet (0.9 meters)
Oil Capacity	1.77 cu in (28.95 cm³)
Fitting Size (End 1)	3/8 inch - 18
Fitting Type (End 1)	NPTF (Male)
Fitting Size (End 2)	3/8 inch - 18
Fitting Type (End 2)	NPTF (Male)
Strain Relief Protection	Vinyl strain relief guards on both ends
Net Product Weight	1.54 lbs (0.7 kg)

CLIN 0033

ENERPAC Hydraulic Oil: HF-101, 1 gal, Jug, ISO Grade 32, Blue



ENERPAC Hydraulic Oil: HF-101, 1 gal, Jug, ISO Grade 32, Blue

Qty: 2 EA

Brand

ENERPAC

MFR / Part #

HF101

SPECIFICATIONS

Manufacturer Model	HF101
Grainger Item Number	3KD76
Product Series	HF-Series (HF-101 Series)
Fluid / Base Oil Type	Premium Petroleum Base with Synthetic Components
ISO Viscosity Grade	ISO VG 32
Equivalent SAE Grade	10W
Fluid Color	Blue (Mavi)
Container Size	1 Gallon (3.78 Liters)
Container Type	Jug (Bidon)
Viscosity Index	100
Viscosity @ 100°F (40°C)	150 – 165 SUS (30 – 32 cSt)
Viscosity @ 210°F (100°C)	42 – 45 SUS (5.3 – 5.4 cSt)
Specific Gravity	0.85
Flash Point (ASTM D92)	375°F (190°C)
Pour Point	-25°F to -37°F (-31°C to -38°C)
Operating Temperature Range	32°F to 149°F (0°C to 65°C)
Lubricant Additives	Zinc, Anti-rust, Anti-foam, Anti-sludge, Anti-oxidation
Zinc-Free	No (Çinko katk Á1d "•
Primary Application	Formulated specifically for High-Pressure Powered Pumps

CLIN 0034

Cottam Wood 37mm Steel Wire Brush, For Engineering, General Cleaning, Rust Remover



Cottam Wood 37mm Steel Wire Brush, For Engineering, General Cleaning, Rust Remover

Qty: 2 EA

Brand

Cottam

MFR / Part #

822-614

SPECIFICATIONS

Brush Type	Heavy Duty Brush
Application	Engineering, General Cleaning, Rust Remover
Bristle Material	Steel
Bristle Length	37mm
Brush Diameter or Width	51mm
Brush Depth	290mm
Number of Rows	4
Colour	Wood

CLIN 0035

RS PRO Stainless Steel Circular Abrasive Brush, 50mm Diameter



RS PRO Stainless Steel Circular Abrasive Brush, 50mm Diameter

Qty: 2 EA

Brand

RS PRO

MFR / Part #

188-4131

SPECIFICATIONS

Brush Type	Circular
Bristle Material	Stainless Steel
Diameter	50mm
Fixing Size	6mm

CLIN 0036

RS PRO Circular Abrasive Brush, 25mm Diameter



RS PRO Circular Abrasive Brush, 25mm Diameter

Qty: 2 EA
Brand
RS PRO
MFR / Part #
188-4097

SPECIFICATIONS

Brush Type	Circular
Diameter	25mm
Fixing Size	6mm

CLIN 0037

RS PRO Steel Bevelled Abrasive Brush, 150mm Diameter



RS PRO Steel Bevelled Abrasive Brush, 150mm Diameter

Qty: 2 EA
Brand
RS PRO
MFR / Part #
188-4120

SPECIFICATIONS

Brush Type	Bevelled
Bristle Material	Steel
Diameter	150mm

CLIN 0038LEATHERMAN Knife: 2 1/2 in Blade Lg, 3 1/2 in Closed Lg, 5 3/4 in Overall Lg, Aluminum, Drop Point



LEATHERMAN Knife: 2 1/2 in Blade Lg, 3 1/2 in Closed Lg, 5 3/4 in Overall Lg, Aluminum, Drop Point

Qty: 2 EA

Brand

LEATHERMAN

MFR / Part #

833164

SPECIFICATIONS

Manufacturer Model	833164
Grainger Item Number	879AW3
Product Series	Skeletool® Series (KBx Variant)
Blade Type	Combo Blade (Partially Serrated)
Blade Shape	Drop Point
Number of Tools / Functions	2
Locking Mechanism	Liner Lock
Blade Material	420HC High-Carbon Stainless Steel
Handle / Body Material	6061-T6 Anodized Aluminum / Type II Cerakote® Finish
Handle Color	Coyote Tan
Clip Material	Stainless Steel with Integrated Bottle Opener
One-Hand Opening	Yes (Thumb Slot)

CLIN 0039North A800 Safety Glasses, Abrasion Resistant, Clear Polycarbonate Lens



North A800 Safety Glasses, Abrasion Resistant, Clear Polycarbonate Lens

Qty: 2 EA

Brand

North

MFR / Part #

1040948

SPECIFICATIONS

Lens Color & Material	Clear, Polycarbonate (PC)
Lens Profile	9-base wrapped panoramic lens, 180° distortion-free field of vision
Lens Coating	Abrasion Resistant (Anti-scratch) and Anti-fog (Fogban) coating
Safety Certification	EN166 (Personal eye protection standard)
Optical Class	Class 1 (Suitable for continuous and permanent all-day use)
Mechanical Strength	F (Low energy impact rating, resists a 6mm steel ball at 45 m/s)
UV Protection	Filters 99.9% of harmful Ultraviolet radiation
Ergonomics & Comfort	Non-slip rubber nose bridge, flexible temples with soft-padded inserts
Weight	Ultra-lightweight construction (22 grams)

CLIN 0040

RS PRO Ultrasonic Cleaner, 200W, 6.5L



RS PRO Ultrasonic Cleaner, 200W, 6.5L


Qty: 1 EA
Brand
RS PRO
MFR / Part #
136-8567

SPECIFICATIONS

Heater Power Rating	200W
Capacity	6.5L
Ultrasonic Power Rating	180W
Height	280mm
Length	325mm
Plug Type	IEC Power Plug
Width	180mm

CLIN 0041

SIP 1.5HP 50L Air Compressor, 8bar, 36kg



SIP 1.5HP 50L Air Compressor, 8bar, 36kg

Qty: 1 EA
Brand
SIP
MFR / Part #
191886

SPECIFICATIONS

Motor Power	1.5 HP (1.1 kW) - 4-Pole Slow-Running Motor
Tank Capacity	50 Liters
Maximum Pressure	8 Bar (116 psi)
Noise Level	59 dB(A) (Ultra-low noise level)
Piston Displacement	8.00 CFM (226 L/min)
Free Air Delivery (FAD)	6.50 CFM (184 L/min)
Pump Type	Twin-cylinder, Oil-free, Direct Drive
Input Voltage	230V / 50Hz (13A supply)
Motor Speed	1450 rpm
Portability	Wheel-mounted design with integrated U-handle
Dimensions (H x W x D)	660 mm x 700 mm x 405 mm
Weight	36 kg

CLIN 0042

AMERICAN FORGE & FOUNDRY Engine Crane: Engine Crane, Steel, 2 ton Load Capacity, 4 Boom Positions



AMERICAN FORGE & FOUNDRY Engine Crane: Engine Crane, Steel, 2 ton Load Capacity, 4 Boom Positions

Qty: 1 EA

Brand

AMERICAN FORGE & FOUNDRY

MFR / Part #

3583

SPECIFICATIONS

Manufacturer Model	3583
Grainger Item Number	817W74
Product Type	Folding Shop Crane / Engine Hoist
Structure Material	Heavy-Duty Gauge Steel
Maximum Load Capacity	2.0 Tons (4,000 lbs / 1,814 kg)
Number of Boom Positions	4
Boom Capacity - Position 1	2.0 Tons (4,000 lbs)
Boom Capacity - Position 2	1.5 Tons (3,000 lbs)
Boom Capacity - Position 3	1.0 Ton (2,000 lbs)
Boom Capacity - Position 4	0.5 Ton (1,000 lbs)
Hydraulic Ram Capacity	8 Tons (Long Ram Jack)
Pump Action	Manual (Single-Acting Hydraulic)
Base Design	Adjustable / Folding Space-Saver Leg Base
Caster Wheel Configuration	6 Heavy-Duty Steel Swivel Casters

CLIN 0043

35' Reinforced Polyurethane Air Hose (Red)



35' Reinforced Polyurethane Air Hose (Red)

Qty: 2 EA

Brand

Reinforced

MFR / Part #

AIRHOSE35

SPECIFICATIONS

Working Pressure, PSI	200 @ 70 °F (21 °C)
Country of Origin	USA
Hose I.D., inches	3/8
Hose Length, feet	35
Temperature Range	-40–165 °F (-40–73.9 °C)
Thread Size	1/4" NPT

CLIN 0044

SPEEDAIRE Air Gun: Thumb-Lever Grip, Chrome-Plated Zinc, 1/4 in Female NPT, 1 Nozzle(s), Straight



SPEEDAIRE Air Gun: Thumb-Lever Grip, Chrome-Plated Zinc, 1/4 in Female NPT, 1 Nozzle(s), Straight

Qty: 2 EA

Brand

SPEEDAIRE

MFR / Part #

22YK47

SPECIFICATIONS

Brand	Speedaire
Mfr. Model	22YK47
Item Number	22YK47
Body Material	Chrome-Plated Zinc
Color	Silver
Control Type	Thumb-Lever Grip
Air Inlet Size	1/4 in Female NPT
Air Outlet Size	1/8 in
Air Consumption	11 SCFM
Maximum Inlet Pressure	150 psi
Nozzle Type	Straight, Brass Safety Nozzle (Non-Marring)
Number of Nozzles	1
Extension Length	1/2 in
Overall Length	3-3/4 in
Airflow Pattern	Focused
Output Thrust	0.7 lbf
Noise Level	102 dB
Standards & Compliance	OSHA 1910.242(b) (Pressure) & OSHA 1910.95 (Noise)

CLIN 0045

RS PRO 25-Piece HSS Thread Tap & Die Set, 1/4 in UNF - 3/4 in UNF Taps, 1/4 in UNF - 3/4 in UNF Dies



RS PRO 25-Piece HSS Thread Tap & Die Set, 1/4 in UNF - 3/4 in UNF Taps, 1/4 in UNF - 3/4 in UNF Dies

Qty: 1 EA
Brand
RS PRO
MFR / Part #
300-7509

SPECIFICATIONS

Maximum Die Size	3/4 in UNF
Minimum Tap Size	1/4 in UNF
Maximum Tap Size	3/4 in UNF
Minimum Die Size	1/4 in UNF
Number of Pieces	25
Set Contents	Taps & Dies
Material	HSS

CLIN 0046

Fluke Multimeter Soft Case for Use with 54II Series, 1577 Series, 51 Series, 53 Series, 1503 Series, 1507 Series, 714



Fluke Multimeter Soft Case for Use with 54II Series, 1577 Series, 51 Series, 53 Series, 1503 Series, 1507 Series, 714

Qty: 2 EA
Brand
Fluke
MFR / Part #
C25

SPECIFICATIONS

Exterior Material	Heavy-duty, high-quality polyester fabric
Interior Features	Protective pocket padding to cushion instruments against drops and shocks
Enclosure Type	Heavy-duty, rugged zippered design
Storage & Organization	Built-in internal pocket to separate and organize test leads and small accessories
Portability	Integrated hand strap / belt loop for hands-free transport
Dimensions (H x W x D)	218 mm x 128 mm x 64 mm (8.6 in x 5.0 in x 2.52 in)
Color Scheme	Standard Fluke corporate layout (Black with Yellow zipper accents)

CLIN 0047

Cantilever Metal tools Box



Cantilever Metal tools Box

Qty: 2 EA
Brand
Blue-Point®
MFR / Part #
KRW48C

SPECIFICATIONS

Country of Origin	CHN
Dimensions, inches	18 x 10 x 13-1/4
Cubic inches (cm³)	1,530 (25,070)
Description/Features	Cantilever Lid (Blue-Point®)
Square inches (cm²)	476 (3,071)

CLIN 0048

Fluke 87V Multimeter Kit



Fluke 87V Multimeter Kit

Qty: 1 EA
Brand
Fluke
MFR / Part #
Fluke 87V + C25 TPAK

SPECIFICATIONS

Model Number	87V
Application	Electrical
Kit Contents	Multimeter,Test Leads, Probes, Holster, Case
Dimensions	201 x 98 x 52mm

CLIN 0049

Fluke 325 - True-RMS



Fluke 325 - True-RMS

Qty: 1 EA
Brand
Fluke
MFR / Part #
Fluke 325

SPECIFICATIONS

AC Response	True-RMS (for non-linear signals)
Backlight	Yes
Data Hold	Yes
Min/Max Function	Yes
Max Wire Diameter	30 mm (600 MCM)
Dimensions (H x W x D)	207 x 75 x 34 mm
Weight	283 g
Safety Category Rating	CAT III 600 V / CAT IV 300 V
Power Supply	2 AAA batteries
Warranty	Two-year

CLIN 0050

Bi mold handle hacksaw



Bi mold handle hacksaw

Qty: 2 EA
Brand
Bi mold
MFR / Part #
HSG319

SPECIFICATIONS

Description	Bi Mold Soft Grip Handle Hacksaw
Country of Origin	SWE
Length, inches	12

CLIN 0051

Hacksaw Blades (10 pk)



Hacksaw Blades (10 pk)

Qty: 1 PACK

Brand

Hacksaw

MFR / Part #

HSBM1224B

SPECIFICATIONS

Country of Origin	SWE
Length, inches	12
Teeth Per Inch (TPI)	24

CLIN 0052

18V XR 2-TOOL PREMIUM BRUSHLESS COMBO KIT-2X POWERSTACK 5AH



18V XR 2-TOOL PREMIUM BRUSHLESS COMBO KIT-2X POWERSTACK 5AH

Qty: 1 EA

Brand

DEWALT

MFR / Part #

DCK2200H2T

SPECIFICATIONS

Kit Model Number	DCK2200H2T
Voltage	18V / 20V MAX*
Motor Type	Brushless (Premium)
Battery Technology	XR POWERSTACK™ (Pouch Cell)
Battery Capacity	5.0 Ah
Quantity of Batteries	2 x DCBP518
Charger Rating	4.0 Amps Fast Charger
Storage Case	TSTAK Heavy-Duty Moduler Case

CLIN 0053

Metal tools Box-5-Drawer Top Chest (Red)



Metal tools Box-5-Drawer Top Chest (Red)

Qty: 2 EA

Brand

SNAP

MFR / Part #

KRA2055FPB0

SPECIFICATIONS

Depth, inches (mm)	14-3/4 (373)
Drawer Banks	1
Width, inches (mm)	26 (660)
Country of Origin	USA
Height, inches (mm)	17-3/16 (436)
Net Weight, lb (kg)	90 (41)
Top Compartment Dimensions, inches (mm)	25-13/16 W x 13-3/4 D x 3-7/8 H (655 W x 348 D x 97 H)
Approx. Square inches (cm²)	1,814 (11,703)
Approx. Cubic inches (cm³)	4,452 (72,955)
Drawer Count	5

CLIN 0054

21 pc High-Speed Jobber Length 118° Point Drill Bit Set (1/16-3/8")



21 pc High-Speed Jobber Length 118° Point Drill Bit Set (1/16-3/8")

Qty: 1 pack

Brand

SNAP

MFR / Part #

DB121C

SPECIFICATIONS

Country of Origin	USA
-------------------	-----

CLIN 0055

29 pc High-Speed Jobber Length 118° Point Drill Bit Set (1/16-1/2")



29 pc High-Speed Jobber Length 118° Point Drill Bit Set (1/16-1/2")

Qty: 1 pack
Brand
SNAP
MFR / Part #
DB129C

SPECIFICATIONS

Country of Origin	USA
-------------------	-----

CLIN 0056

3/4" Drive Heavy-Duty Air Impact Wrench (Red)



3/4" Drive Heavy-Duty Air Impact Wrench (Red)

Qty: 1 EA
Brand
SNAP
MFR / Part #
MG1250

SPECIFICATIONS

Free Speed, RPM	6,200
Sound Pressure Level, dB(A)	99.8
Length, inches (mm)	8 (203)
Vinyl Boot	MG1200BOOT
Air Consumption, Free Speed, CFM (SCFM) [l/min]	6.4 (46) [181]
Air Inlet Thread Size, inches (NPT)	3/8 (18)
Country of Origin	USA
Sound Level dB(A) Pressure	99.8
Blows Per Minute, BPM	1,050
Vibration Level, m/s²	10.38
Recommended Hose Size, inches (mm)	3/8 (10)
Anvil Type	Friction Ring
Drive Size, inches (mm)	3/4 (19)
Weight, lb (kg)	8.1 (3.6)

CLIN 0057

12-5/8" Pliers Wrench



12-5/8" Pliers Wrench

Qty: 1 EA
Brand
SNAP
MFR / Part #
PWZ1DP

SPECIFICATIONS

Dimension B, Jaw Capacity, inches	1-3/4
Dimension A, Length, inches	12-5/8
Country of Origin	ESP
Weight, lb	1-5/8
Dimension C, Jaw Thickness, inches	1/2
Dimension D, Overall Width, inches	3/4

CLIN 0058

8-3/16" Pliers Wrench



8-3/16" Pliers Wrench

Qty: 1 EA
Brand
SNAP
MFR / Part #
PWZ00A

SPECIFICATIONS

Dimension B, Jaw Capacity, inches	1-1/2
Dimension A, Length, inches	8-3/16
Country of Origin	ARG
Weight, lb	1
Dimension C, Jaw Thickness, inches	5/16
Dimension D, Overall Width, inches	9/16

CLIN 0059 24" Aluminum External Pipe Wrench



24" Aluminum External Pipe Wrench

Qty: 1 EA
Brand
SNAP
MFR / Part #
PWA24A

SPECIFICATIONS

Dimension B, Jaw Capacity, inches	3
Dimension A, Length, inches	24
Country of Origin	USA
Style	Aluminum Handle

CLIN 0060 14" Aluminum External Pipe Wrench



14" Aluminum External Pipe Wrench

Qty: 2 EA
Brand
SNAP
MFR / Part #
PWA14A

SPECIFICATIONS

Dimension B, Jaw Capacity, inches	2
Dimension A, Length, inches	14
Country of Origin	USA
Style	Aluminum Handle

CLIN 0061 10" Aluminum External Pipe Wrench



10" Aluminum External Pipe Wrench

Qty: 2 EA
Brand
SNAP
MFR / Part #
PWA10A

SPECIFICATIONS

Dimension B, Jaw Capacity, inches	1-1/2
Dimension A, Length, inches	10
Country of Origin	USA
Style	Aluminum Handle

CLIN 0062

10 pc 12-Point SAE Flank Drive® Plus Combination Wrench Set (5/16, 3/8-7/8")



10 pc 12-Point SAE Flank Drive® Plus Combination Wrench Set (5/16, 3/8-7/8")

Qty: 2 pack
Brand
SNAP
MFR / Part #
S0EX710

SPECIFICATIONS

ASME®	B107.100
Country of Origin	USA

CLIN 0063

8 pc Instinct® Soft Grip Combination Screwdriver Set (Red)



8 pc Instinct® Soft Grip Combination Screwdriver Set (Red)

Qty: 1 EA
Brand
SNAP
MFR / Part #
SGDX80BR

SPECIFICATIONS

Country of Origin	USA
-------------------	-----

CLIN 0064

37 pc 3/8" Drive SAE/Metric General Service Set (Blue-Point®)



37 pc 3/8" Drive SAE/Metric General Service Set (Blue-Point®)

Qty: 1 EA
Brand
Blue-Point®
MFR / Part #
BLPGSS3837

SPECIFICATIONS

Country of Origin	TWN
-------------------	-----

CLIN 0065

38 pc 1/4" Drive General Service Set (Blue-Point®)



38 pc 1/4" Drive General Service Set (Blue-Point®)

Qty: 2 pack
Brand
Blue-Point®
MFR / Part #
BLPGSS1438

SPECIFICATIONS

Country of Origin	TWN
-------------------	-----

CLIN 0066

18 V Blower (Tool Only) (Red)



18 V Blower (Tool Only) (Red)

Qty: 1 EA
Brand
SNAP
MFR / Part #
CTAB9050

SPECIFICATIONS

oltage	18
Speed, RPM	14,800
Country of Origin	CHN
Maximum Air Speed, MPH	100
Maximum Air Volume, CFM	450
Battery (qty)	CTB8187 (Not Included)
Weight, lb	6
Length, inches	31
Battery Charger	CTC131A (Not Included)
Weight (with battery), lb	7.75

CLIN 0067

DeWALT DCB1104D2-QW 2 Ah 18V Battery & Charger, For Use With 18V XR Lithium-ion DEWALT Tools

Image
unavailable

View online !—

DeWALT DCB1104D2-QW 2 Ah 18V Battery & Charger, For Use With 18V XR Lithium-ion DEWALT Tools

Qty: 1 pack

Brand

DeWALT

MFR / Part #

DCB1104D2-QW

SPECIFICATIONS

Battery Voltage	18V XR
Battery Capacity	2.0 Ah
Battery Energy Capacity	36 Wh
Included Batteries	2 x DCB183 Lithium-Ion
Battery Chemistry	Lithium-Ion (XR Series)
Charger Model	DCB1104
Charger Charging Output	4.0 A
Charger Input Voltage	230 V (AC)
Charger Plug Configuration	Type-F (Continental European 2-pin Schuko)
Compatibility	All DEWALT 10.8V, 14.4V, and 18V XR Li-Ion Batteries
Dimensions (Battery - mm)	Approx. 110 mm x 75 mm x 45 mm
Dimensions (Charger - mm)	Approx. 145 mm x 115 mm x 70 mm
Operating Temperature Range	-10°C to +40°C

Binding Effect

This Statement of Work (SOW) is issued as Annex A to the Financial Proposal for Tender TND-2026-0268 and forms an integral part of any resulting offer. By signing the accompanying Financial Proposal, the Supplier confirms it has reviewed this Annex in full and that its commercial offer is based on, and compliant with, the technical requirements set out herein.

Supplier Acknowledgement

Company Name

Authorized Representative

Signature

Date